

ENGINE

- John Deere® PE4045HFG92 - turbocharged, diesel engine
 - Prime - 97 hp @ 1800 rpm
 - Standby - 107 hp @ 1800 rpm
 - 4 cylinder
 - 4.5 L displacement
 - Interim Tier IV approved
- Steel, single wall fuel tank
 - 165 gal. (625 L) capacity
 - 31 hr. run time – full load
 - Fuel tank built into skid of generator set
- Cooling system capable of operating at 120°F (49°C) ambient
- Radiator and oil drains plumbed to exterior
- Rubber vibration dampers isolate engine/generator from frame
- Disposable air filter - paper element
- 60 Hz engine/generator
- Electronic isochronous governing

GENERATOR

- Marathon Electric®
 - Brushless
 - 4 pole
 - Class H insulation
- Voltage regulation +/- 0.5% with Magnum PM600 Voltage Regulator

SYSTEM OUTPUTS

- 3 position selector switch
 - Single phase – 120 / 240V Zig Zag
 - Three phase – 120 / 208V Low Wye
 - Three phase – 277 / 480V High Wye
- 60 kW / 60 kVA – standby, single phase
- 56 kW / 56 kVA – prime, single phase
- 69 kW / 86 kVA – standby, three phase
- 62 kW / 77 kVA – prime, three phase

SYSTEM CONTROLS

- Power Zone® controller and display
 - Backlit, 800 x 480 pixel resolution color display
 - -40°F to 185°F (-40°C to 85°C) operating temperature range
 - Automatic coarse voltage adjustment
 - Integrated fine voltage adjustment
 - PLC functionality

SYSTEM CONTROLS (continued)

- Push buttons for easy operation
 - Manual or Auto Start
 - Engine Start
 - Engine Stop/Reset
 - Alarm Mute
 - Operator Screens
 - Home
 - Engine
 - Generator
 - Voltage Adjust
 - Scrolling Arrows for Diagnostic Information
 - Engine diagnostic display
 - Oil pressure
 - Engine temperature
 - Fuel level
 - Battery
 - After treatment inlet/outlet temperature
 - Ash/soot levels
 - Generator diagnostic display
 - System kW output display
 - Line output & frequency display
 - Alarms
 - Warning
 - Shutdown
 - Electrical Trip
 - Engine
 - Alarm list – warnings / shutdowns; 250 event history log – date/time stamp
 - Fuel level: warning – 15%; shutdown – 5%
 - Over speed protection: shutdown – 115%
 - Oil pressure: warning – 25 psi; shutdown – 20 psi
 - Coolant temperature: warning – 220°F (104°C); shutdown – 230°F (110°C)
 - Battery voltage: over – 15VDC; under – 11VDC
 - Generator over voltage: warning – 110%; electrical trip – 111%
 - Generator under voltage: warning – 87%; electrical trip – 86%
 - Generator over frequency: warning – 105%; electrical trip – 110%
 - Generator under frequency: warning – 95%; electrical trip – 90%
 - Inputs/Outputs
 - Auto Schedule
 - Status
- Configuration of controller, firmware and connections

ELECTRICAL CONTROLS

- Remote start / stop contacts located in lug box
- Lockable control box door with diagnostics window
- Lockable lug box with safety switch
 - Trips main breaker when door is opened
 - Disables voltage regulator
- Output ground connection lug inside lug box
- 300A main breaker with shunt trip
- Convenience receptacles with individual breakers (restricted use in high wye mode)
 - (2) 120V 20 Amp GFCI duplex outlets – (NEMA 5-20R type)
 - (3) 125 / 250V 50 Amp, 3 pole, 4 wire Twistlock (Non-NEMA 6369)
- Voltage adjustment integrated into Power Zone controller, +/- 10%
- 720CCA wet cell battery

ENCLOSURE

- Aluminum, sound attenuated enclosure
 - UV & fade resistant, high temperature cured, white polyester powder paint
 - Insulated and baffled
 - 68 dB(A) @ 23 ft. (7 m) – prime power
- Fully lockable enclosure including doors and fuel fill
- Emergency stop switch located on outside of enclosure
- Central lifting point
- Multi-lingual operating/safety decals
- Document holder with operating manual including AC/DC wiring diagrams

TRAILER

- DOT approved tail, side, brake, and directional lights; recessed rear lights
- Transportation tie downs
- Safety chains with spring loaded safety hooks
- 3 in. (76.2 mm) lunette ring hitch
- 6000 lb. (2722 kg) axle with surge brakes
- 3000 lb. (1361 kg) tongue jack with footplate
- ST225/75R15 tubeless tires – 8 ply

WEIGHT & DIMENSIONS

- Skid mounted
 - Dry weight: 3530 lbs. (1600 kg)
 - Operating weight: 4700 lbs. (2131 kg)
 - 119 x 40 x 62 in. (3.02 x 1.02 x 1.57 m)
- Trailer mounted
 - Dry weight: 4240 lbs. (1923 kg)
 - Operating weight: 5410 lbs. (2454 kg)
 - 170 x 69 x 80 in. (4.32 x 1.75 x 2.03 m)

WARRANTY

2 Years / 2000 Hours

CERTIFICATIONS

CSA Certified